

M500TT **Intermec**®

Dispenser like applicator with Intermec printer

- Intermec reliable and rugged printers based side and top applicator
- M500TT offers all Intermec printer functionality with wide range of ready to use software
- M500TT enables printing from Windows or Unix based program in network



MICROSTYR + INTERMEC =



M500TT

Product data

Application

- Direct Thermal (DT) and Thermal Transfer (TT) printing of adhesive labels, tickets and tags.

Physical Characteristics

- LxHxW: 900 x 300 x 480 mm
- Weight: 15 kg

Print Specifications

- Max. Print Width: 104mm (4.09 in)

Print Speed

- Print speed up to 120 labels/min

Available software

- Intermec Printer Application Server™
- ERPLabel™ for SAP™ R/3®.

Print Resolution

- 8 dots/mm (203 dpi),
- 11.8 dots/mm (300 dpi)

Label/Ticket/Tag

- Max. Width: 104 mm (4.09 in)
- Thickness: 60 to 250µm (2.4 to 10 mil)
- Label Roll max diameter: 213 mm (8.38 in)
- Label Roll Core: 38-76 mm (1.5-3.0 in)

Ribbon Roll

- Ribbon roll max diameter: 83 mm (3.27 in) corresponding up to 450 m (1475 ft) in length
- Ribbon Roll Core: 25 mm (1.0 in)
- Ribbon Type: Wax, wax/resin, resin

Standard Interfaces:

- RS-232, up to 115.2 kB/s
- USB 1.1
- EasyLAN Internal Ethernet 100/10BaseT
- I2C-bus for cutter
- Wand interface for EasySet™ System

Optional interface:

- EasyLAN Wireless, internal 802.11b/g Wireless Ethernet

ok