

Stripe® S600™

Thermal, On-demand Bar Code Printer

Weighing less than 8kg this economical, full-size printer is in a class all of its own.

With a Zebra S600 printer, you can count on consistent, reliable performance. The S600 features state-of-the-art technology, including the ZebraLink™ real-time connectivity and control solution. It can accommodate a full-sized roll of media within the printer, minimising media maintenance and label contamination by airborne dust or moisture.

Affordable Team Player

Lightweight, yet highly durable, this printer can be easily moved from one workstation to the next, anywhere it's required. Or purchase more than one extremely affordable printer for distributed printing throughout your company.



Reliability on demand™



Stripe® S600™

Full-size, Economical Printer

- Full-size, 203 mm (8") O.D. media roll accommodation
- Multiple media handling options (e.g. cutter, rewind)
- Affordably priced

Simple, Reliable Operation

- Easy-to-use, colour-coded operator cues
- Innovative, ribbon release mechanism for simplified ribbon replacement
- Toggle-pressure printhead for optimum print quality

State-of-the-art Technology

- ZebraLink real-time connectivity and control solution
- Flash memory
- Auto-calibration
- Auto-synchronisation of serial port
- Standard bar code and 2D symbology algorithms reside in memory for faster printing

For further information on these products, please visit the Zebra web site at: www.zebra.com



Zebra Technologies

European Headquarters

Zebra House, The Valley Centre
Gordon Road, High Wycombe
Buckinghamshire HP13 6EQ
United Kingdom
Tel: +44 (0)1494 472872
Fax: +44 (0)1494 450103

Regional Sales Office

Mollsfeld 1
D-40670 Meerbusch
Germany
Tel: +49 (0) 2159 6768 0
Fax: +49 (0) 2159 6768 22

Regional Sales Office

50 rue Marcel Dassault
F-92100 Boulogne-Billancourt
France
Tel: +33 (0)1 55 20 93 93
Fax: +33 (0)1 55 20 93 99

International Headquarters

333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109
USA
Tel: +1 847 793 2600
Fax: +1 847 913 8766

Other Locations

United States: California, Florida, Rhode Island, Wisconsin

Europe: Italy, the Netherlands, Poland, Spain, Sweden

Asia-Pacific: Australia, China, Japan, Singapore, South Korea

Middle East: Dubai



© 2005 Zebra Technologies Europe Limited
Printed in the UK

FS-30902
An ISO 9000 registered company

#12516L Rev. 4 (08/05)

Specifications at a Glance*

Standard Features

- Print methods: Thermal transfer or direct thermal
- Construction: Polycarbonate plastic case
- ZebraLink and web Alert
- Smooth scalable fonts
- 18 standard bar codes and seven two-dimensional symbologies resident in printer
- Label tear-off feature
- Transmissive sensor
- Fully enclosed 203 mm (8") O.D. media compartment
- Zebra's E³ Printhead Energy Control
- Auto-calibration
- Auto-synchronisation of serial port
- ZPL II[®] — Universal language for Zebra printers

Operating Characteristics

Environment

- Operating Temp. 40°F/5°C to 105°F/40°C
- Storage/Environment -40°F/-40°C to 140°F/60°C
- Operating Humidity 20-85% non-condensing
- Storage Humidity 5-85% non-condensing

Electrical

- Internal automatic switching power supply 110VAC +/-20%, 230VAC +/-15%, 47-63Hz

Media Characteristics

Labels

- Max. Roll Size
- 203 mm (8") O.D. on a 76 mm (3") I.D. core

Thickness (label & liner)
.058 mm (.0023") – .305 mm (.012")

Media Types

- Continuous or fanfold, die-cut, black mark, perforated, notched, tag stock

For optimum print quality and printer performance, use genuine Zebra supplies.

Fonts/Graphics/Symbologies

Fonts and Character Sets

- Standard Fonts: 14 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
- Sets: IBM® Code Page 850 International character set
- Optional European and Asian font sets

Graphic Features

- Supports user-defined fonts and graphics – including custom logos
- ZPL II drawing commands – including boxes and lines

Options and Accessories

- 8MB Flash memory with real-time clock
- Cutter; Label peel-off
- Reflective media sensor
- ZebraNet® PrintServer II (external)
- ZebraNet 10/100 Print Server (external)
- European and Asian font sets

* Specifications listed are for base model printers with standard features only unless otherwise noted. Specification subject to change without notice.

© 2005 Zebra Technologies Europe Limited. Reliability on demand, ZebraDesigner, ZebraLink, ZebraNet, Element Energy Equalizer and all product names and numbers are Zebra trademarks, and Zebra, representation of the Zebra Head, ZebraNet, E³ and ZPL II are registered trademarks of Zebra Technologies Europe Limited. All rights reserved. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. IBM is a registered trademark of International Business Machines Corporation. UFST is a registered trademark of Agfa Monotype Corporation. All other trademarks are the property of their respective owners.



S 6 0 0

ZebraLink™

ZebraLink Solutions

Software

ZebraDesigner™ Pro
ZebraNet™ Bridge Enterprise
ZebraNet Utilities v 7.0
Zebra Universal Driver
European and Asian font sets

Networking

ZebraNet 10/100 Print Server (external)
ZebraNet PrintServer II (external)

Firmware

ZPL II[®] – Universal language for Zebra printers. Simplifies label formatting and enables format compatibility with other Zebra printers.

Web View – Enables you to connect and control your bar code printer's Web interface using a common Web browser.

Alert – Printers equipped with ZebraNet print servers will notify you via any email-enabled, wired, or wireless device to minimize downtime.

The S600™ is perfect for moderate printing needs in commercial or light industrial applications, including:

- Professional/Business offices
- Incoming product labelling
- Hospitals and healthcare; medical laboratories
- Receipts and ticketing
- On-demand shipping labels and parts tracking

Maximum Print Area

Width: 104 mm (4.09")
Length (with standard memory):
991 mm (39")

Resolution

8 dots per mm (203 dpi)

Maximum Print Speed

152 mm (6") per second

Memory

Standard:
1MB Flash, 2MB DRAM (S600)
Optional: 8MB Flash with real-time clock

Physical Characteristics

Width: 210 mm (8.25")
Depth: 432 mm (17")
Height: 330 mm (13")
Weight: 7.71 kg (17lbs)

Media Specifications

Label and liner width:
19 mm (.75") to 114 mm (4.5")
Ribbon width:
40 mm (1.57") to 114 mm (4.5")